

**Battery type : AGM B170 SL**  
Deep Cycle Batteries  
Absorbent Glass Mat [AGM]

12V 170AH C100[10,8V]  
Dimensions : mm 513 x 223 x 223h

" SL " range features advanced AGM technology with absorbed electrolyte. Designed for reliable storage solutions for renewable energy application.

- Deep Cycle AGM Batteries 12V
- Valve Regulated Battery
- 100% non spillable, perfect for indoor usage
- More than 500 cycles at 75% D.O.D.
- More than 1000 cycles according to IEC 61427 (PVES Applications)
- Extremely long service life
- Absolutely maintenance-free
- High reliability and safe handling
- Flat Plates
- Fully recycable

Application Areas:

Small Solar and Wind power stations  
Small size industrial solar systems  
Street solar lighting  
Caravans, Boats, Yachts


### Technical Parameters 12V blocks

C1 [10,2V per block]	C5 [10,2V per block]	C10 [10,2V per block]	C100 [10,8V per block]	Reserve Capacity min	Constant power discharge for 15 min [W per block]
Ah	Ah	Ah	Ah		
100	130	145	170	300	2700

### Charging Parameters

Charging type	Parameter / Limits
Charge with constant current	Current limit: 10 - 20 % from C10 capacity rate
Charge with constant voltage	Voltage limit: 14.1 - 15.0 V per block
Float Charge Voltage (cycling)	Float voltage: 13.62 V per block @ 20°
Temperature Correction Factor	0.018 V per block / °C

### Layout



### Terminal

